


FIREPRO

FIRE PROTECTIVE BUILDING PRODUCTS

HEAD OFFICE: AUCKLAND (09) 579 0367
WELLINGTON (04) 568 7086 • CHRISTCHURCH (03) 379 9364
www.firepro.co.nz sales@firepro.co.nz

CI/SfB



C623 DATASHEET - AUG08

Product specifications
can change. Contact
us to ensure you have
our latest datasheet

FIREPRO C623 TOPSEAL

C623 is a high quality single pack 100% pure acrylic finish coat approved for use as part of Firepro Intumescent Coating Systems for the fire rating of structural steel. This topsealer is not in itself a fire protective coating.

C623 is a coating formulated to provide chemical, abrasion and weather resistance. C623 is available in gloss and semi-gloss finish, stocked in white gloss, may be tinted to BS colours.

SURFACE PREPARATION

Ensure the Firepro intumescent base is completely dry, and free from all contaminants, and has been applied in accordance with the applicable Application Notes.

SOLVENT

Water.

METHOD OF APPLICATION

Spray is preferred for best finish and the best edge protection.
Small areas may be brushed.
Clean-up: Water.

APPLICATION TEMPERATURES

Do not apply below 10°C.

THEORETICAL COVERAGE

8 square metres per litre. DFT 40µm

DRYING TIME

3 to 6 hours depending upon temperature and ventilation.

*NOTE: The technical information and suggestions for use and application presented herein represent the best information available to us and are believed to be reliable. They should not however be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine final suitability for their specific end uses. All dimensions are nominal. **We reserve the right to make changes or to withdraw designs and products without notice.***